

DIGIEVER Network Camera Compatibility List

The list is applied for DIGIEVER NVR firmware 76 version or later

Update: Jan. 2024

- DIGIEVER NVR supports the camera feature
 - * Camera does not support the feature
 - Ⓟ 360° Panoramic
 - Ⓢ NVR support camera hardware dewarp
 - Ⓣ NVR support camera software dewarp
 - ◆ Camera takes more than 1CH, needed to be added via video sever method
 - Blank means the feature is NOT supported or verified by DIGIEVER
- | | | |
|--------------------|------------------------------|------------------------------------|
| 1. Audio Detection | 5. Intrusion Detection | 9. People Counting Threshold Alarm |
| IVA Event | 2. Advanced Motion Detection | 6. Loitering Detection |
| No.: | 3. Human Detection | 7. Foreign Object Detection |
| | 4. Cross Line Detection | 8. Missing Object Detection |
| | | 10. Temperature Detection |
| | | 11. Camera Tampering Detection |
| | | 12. Object Status Change |

Supported in the NVR latest version
 Copyright © DIGIEVER Corporation All Rights Reserved * Please contact DIGIEVER sales for updated information

Brand	Camera Model	Compression				Zoom Control			Motion Detection	Digital Input	Audio (Besides HTTP)	Two-way Audio	Edge Record (RTSP)	Supported IVA	Advanced Right-Click Menu	Camera Firmware/ Note
		MJPEG	MPEG -4	H.264	H.265	Pan/Tilt	Optical Zoom	Digital Zoom								
intelbras	(DIGIEVER NVR supports intelbras cameras with audio format: G711)															
	intelbras VIP BX 1M	●	●	●	*	*	*	●	●	●	●					
	intelbras VIP CB 1M	●	●	●	*	*	*	●	●	*	●					
	intelbras VIP DM1 MIR VF	●	●	●	*	*	*	●	●	●	●					

- Note:**
- More models are under integration and will be released soon.
 - Two-way audio: ACTi, AXIS, Brickcom, Canon, Hi-Sharp, Honeywell, Levelone, Milesight, Risk Captur, SONY, TOA (5-generation camera), VIVOTEK (LAN), WatchNet
 - Edge recording: ACTi, AXIS (H.264 only), Brickcom, Dynacolor, Honeywell, Hunt, SONY(H.264 only), VIVOTEK, WatchNet
 - VB Search supports Canon cameras listed in the compatible list except VB-C series.
 - Local liveview supports ImmerVersion engine codec of H.264 and MJPEG only.
 - For camera added via ONVIF protocol, please follow below steps to set up camera event (like motion detection, digital input, tampering detection) on DIGIEVER:
 - On DIGIEVER NVR: Enable camera event on event and action management page.
 - On camera webpage: Enable camera event on camera setting page
 - NVR supports H.264 and H.265 through ONVIF. For MJPEG format, please use Generic_MJPEG to add the camera.
 - NVR supports Honeywell IVA through ONVIF (by Model): Motion Detection, Advanced Motion Detection, Tampering Detection, Intrusion Detection, Loitering Detection, People Counting Threshold Notice
 - Cameras are not supported in Camera Digital Output in the Event & Action Management : Canon and TOA

Copyright © DIGIEVER Corporation All Rights Reserved

- ✂ Camera IVA event support list:
- Audio detection:** ACTi, AXIS
 - Advanced motion detection:** AXIS, Hanwha, Hitron, Milesight, WatchNet
 - Human detection:** ACTi, AXIS, Hanwha, Levelone, Milesight, WatchNet
 - Cross line detection:** AXIS, Brickcom, Canon, Hanwha, Hikvision, Honeywell, Levelone, Milesight, Risk Captur, WatchNet
(Note: If camera resolution is higher than 4K, local display doesn't support tripwire.)
 - Intrusion detection:** ACTi, AXIS, Brickcom (specific version), Hitron, Honeywell, Risk Captur
 - Loitering detection:** AXIS, Brickcom (specific version), Honeywell, Milesight, Risk Captur, WatchNet
 - Foreign object detection:** AXIS, Brickcom (specific version), Hitron
 - Missing object detection:** ACTi, AXIS, Brickcom (specific version), Hitron
 - People counting threshold alarm:** AXIS, Hanwha, Honeywell, Milesight, Risk Captur, VIVOTEK, WatchNet
 - Temperature detection:** EOC, FLIR, Honeywell, Mobotix
 - Camera tampering detection:** Axis, EOC, Hitron, Honeywell, Milesight, WatchNet
 - Object Status Change:** Axis, Dahua